

# RF5108WKK1-433 Wireless Key Kit



## Product Features:

- ▶ Ideal for those applications where only a few wireless keys and zones are required
- ▶ 433 MHz wireless receiver
- ▶ Supports up to eight wireless keys (without taking up a zone slot) and eight wireless detectors
- ▶ Small, compact design
- ▶ Includes an internal antenna
- ▶ KEYBUS compatible with PowerSeries™ control panels
- ▶ Two on-board, fully programmable (50 mA) outputs
- ▶ LED switch plate (single-gang) provided
- ▶ WS4939 four-button wireless key included
- ▶ UL/ULC and CE approved

## RF5108WKK1-433



**Useful for those applications where coverage of a large area is not required, the RF5108WKK1-433 wireless key kit can simultaneously support up to eight wireless detection devices and eight wireless keys without taking up a zone slot.**

The RF5108-433 wireless receiver of the kit easily expands any DSC hardwired system by adding coverage to areas that are difficult or impossible to reach with conventional wiring. The RF5108WKK1-433 wireless key kit is ideal for small- to mid-size installations.



[www.dsc.com](http://www.dsc.com)  
1-888-888-7838

# RF5108WKK1-433 Wireless Key Kit



## Easy Installation

To help reduce installation times, the wireless key receiver features an internal antenna and connection to the control panel via a four-wire KEYBUS.

## Value Added

The RF5108WKK1-433 features two on-board 50 mA programmable outputs that can be used to trigger the LED switch plate (single-gang) that is included with the kit or be programmed to perform other tasks, such as activating garage door openers, turning on lights or opening powered gates.

## WS4939 Wireless Key

The WS4939 four-button wireless key included with the kits adds convenience and value to any DSC security system. These multi-purpose devices include activation delays and can be used to arm/disarm any PowerSeries™ security system from a distance. To trigger the arm/disarm function, you must press and hold the appropriate button for one second, and for the panic function, three seconds. An integrated LED indicator signifies to the user that a transmission has been sent to the security system.

## Compatibility

The RF5108WKK1-433 is compatible with all DSC 433 MHz devices and the following control panels:

- Power432™ PC580/585
- Power632™ PC1555/1565
- Power832® PC5010
- Power864™ PC5020

## Specifications

- Dimensions ..... 4 1/4" x 3 1/8" x 1"  
(108 mm x 78 mm x 25 mm)
- Voltage ..... 12 Vdc
- Current Draw ..... 40 mA (Typical)
- Operating Environment ..... 32° to 120° F  
(0° to 49° C)
- Relative Humidity ..... 5% to 93%

### Ordering Information:

RF5108WKK1-433	Wireless Key Receiver
WS4939	4-Button Wireless Key